



PI-Mag™ Care Tips Guide

Surface Preparation Tips

Only apply magnetic sheet to a surface that has been waxed or cured. Do not apply magnetic sheet to a surface that has been freshly painted or repainted less than 90 days ago. Only apply material to dry surfaces. For best results, wax the surface before each application.

Magnetic Sheet Application

Apply magnetic material to flat surfaces that are not in direct sunlight. Smooth the material to make sure it is completely flat. If the material needs to be readjusted, remove the material and reapply it. Do not slide the material into place when it is already against a metal surface as it can cause marring. Avoid hoods and trunks because these areas reach high temperatures beyond the 150 degrees F (65 degrees C) that the magnet can withstand. Again, it is very important to remove the magnetic material daily and avoid long term application to your vehicle without removing the material. This can cause the area where the material is applied to fade slower than the rest of the car.

Recommended Daily Preparation

Although the magnet is flat against a metal surface, moisture and dirt can still build up between the magnet and the metal surface. Remove the magnet daily and wipe off the magnet and the metal surface with a soft cloth with a gentle detergent and water mixture. Let both surfaces dry completely and reapply wax to the surface before apply the magnetic sheet to the surface. It is very important to make sure that any painted surface or treated surface i.e. colored paint, clear coat, and wax surfaces be cured. All newly painted surfaces require 90 days before magnetic material can be applied. Do not use on repainted surfaces.

Storing Flexible Magnetic Sheet

It is recommended to store roll material at room temperature in a closed box. This will keep metal particles from collecting on the material. Printed and laminated material should be rolled up with the print or laminate facing out to prevent wrinkles on that surface. Sheeted material should have spacers between each sheet like cardboard or wax paper and covered.

Liability and Warranty Information—Please Read!

It is strongly recommended to follow the instructions mentioned above. Magnet Products International cannot be held responsible for any damage resulting from misuse or failure to follow the guidelines mentioned above. Failure to apply the magnetic sheeting properly may result in damage to the vehicle paint surface along with damage to the magnetic sheeting. Magnet Products International warrants to the Buyer for a period of 30 days from date of shipment that our product will be free of any defects in material and workmanship. Magnet Products International makes no other warranties about our products, express or implied including without limitation the implied warranty of fitness for a specific use. Before using, user shall determine the suitability of the product for its primary use and user assumes all risk and liability whatsoever in connection herewithin. Neither seller nor manufacturer shall be liable in tort or in contract for any loss or damage, direct, incidental, or consequential arising out of the use or inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of the seller and manufacturer. In the event the seller does not deliver product that's conform to the warranties set forth above, seller at its own discretion repair or replace defective material. The foregoing remedy for repair or replacement is Buyer's exclusive remedy for breach of warranty explained above.